

YARD RAMP

Portable Steel Yard Ramp

Our Steel Yard Ramp moves with ease into position at trailers, railcars, or docks. The operator then utilizes a self-contained, double-acting hydraulic pump to adjust the unit to the proper position. In minutes you are ready to load or unload freight. Solid 18" rubber tires provide easy positioning and towing. Open serrated steel grating provides excellent traction while preventing build-up of snow, water, and other debris. Beveled approach and exit provides a smooth transition. For truck or railcar to ground applications choose a 36' unit including a level off. Choose a 30' straight design for quick loading from dock to ground.



Hydraulic Pump System

The dual cylinder hydraulic system allows for smooth and quick raising of the front lip to the proper dock or trailer height. Simply open the release valve to safely lower the unit into position. The pump is mounted internally to protect it from accidental damage.

Product Features

- All steel welded construction
- Steel serrated grating
- Double-action hydraulic pump
- Capacities from 16,000 to 60,000 pounds
- Wide range of capacities and sizes available
- Solid rubber tires standard, pneumatic tires optional



DOCKPLATES



Aluminum Dockplate

Recommended for non powered dock loading applications only

- Available in two capacity ranges
- Low-cost solution to light dock loading activity applications
- Bolt-on steel legs for securing position between the dock and the trailer

The lip bend is 11° on every aluminum dockplate. The standard lip length for conventional trailers is 11", with an option of 14" lip length for refrigerated truck applications. Aluminum dock plates are designed to work well with pallet trucks or other non-powered dock loading equipment. The machine beveled deck edges allow for smooth transition between the truck and the loading dock.

DOCKBOARDS

Aluminum Dockboard

- Capacities from 10,000 to 15,000 pounds
- Full-length structural steel bolt-on curbs

Our Aluminum Dockboards have steel curbs bolted to the aluminum diamond pattern plate for increased strength, and to help prevent runoff. The locking legs provide secure positioning when in use. Our Aluminum Dockboards have a lip bend of 11°. Standard lip length for conventional trailers is 11", but we have an option of 14" for refrigerated applications. The Dockboards come in widths from 60 inches to 72 inches, and lengths from 36 inches to 96 inches.

Steel Dockboard

- Capacities from 10,000 to 20,000 lbs
- Ideal for Electric or Gas powered forklift loading applications

All Handi-Ramp welded steel dockboards provide a safe ramp for heavy-duty loading dock applications. Selecting the proper Handi-Ramp dockboard product for your application will improve product life, safety, and loading dock efficiency.

